

# MODEL ZW209FP- Fire Protection Pressure Reducing Valve Control Valve Order Form



Customer: \_\_\_\_\_

Date: \_\_\_\_\_

Contact: \_\_\_\_\_

Email: \_\_\_\_\_

Telephone/Fax: \_\_\_\_\_

Ref. P. O. \_\_\_\_\_

## Required Valve Information

Quantity: \_\_\_\_\_

All returns are subject to a restocking/refurbishing fee.  
Contact Customer Care for details on return policies.

Size: (Check one)  1-1/4" (DN32)  1-1/2" (DN40)  2" (DN50)  2-1/2" (DN65)  3" (DN80)  
 4" (DN100)  6" (DN150)  8" (DN200)  10" (DN250)

### Function Options:

Optional  "C" Option\* - 40XL Hydraulic Check

**Valve body is ductile iron, epoxy coated**


### Body Options:

Check one  Standard - Full Port Globe Body  
 "A" Option - Angle Style Body

### End Connections (Check one)

Options	Description	Options	Description
<input type="checkbox"/> "X"	- ANSI Class 150 Flanges	<input type="checkbox"/> "PN6"	- ISO Class PN6 Flanges
<input type="checkbox"/> "BSD"	- BS10/AS2129 Table D Flanges	<input type="checkbox"/> "PN10"	- ISO Class PN10 Flanges
<input type="checkbox"/> "BSE"	- BS10/AS2129 Table E Flanges	<input type="checkbox"/> "PN16"	- ISO Class PN16 Flanges
<input type="checkbox"/> "BSF"*	- BS10/AS2129 Table F Flanges	<input type="checkbox"/> "PN25"*	- ISO Class PN25 Flanges
<input type="checkbox"/> "BSH"*	- BS10/AS2129 Table H Flanges		
<input type="checkbox"/> "G"	- IPS Grooved, ANSI/AWWA C 606		
<input type="checkbox"/> "BG"	- Grooved 2-1/2", or 6" (76.1 mm or 165.1mm pipe OD)		
<input type="checkbox"/> "Y"*	- ANSI Class 300 Flanges		

### Size Range (1-1/2" - 10", DN40 - DN250)



### Size Range (1-1/4" - 3", DN32 - DN80)

"TH" - NPT Threaded, ANSI/ASME B1.20.1  
 "BS" - Threaded British Pipe Parallel BSPP/G size ISO  
 "BT" - Threaded British Pipe Tapered BSPT/Rc size ISO



### Main Valve Option:

Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide  
Optional  "Z" Option\* - Visual Position Indicator

### Pilot Options:

Standard - 3-Way Gauge Isolation Valves, Inlet and Outlet Pressure Gauges (UL) and "Wye" Type Strainer  
 Standard - PV-PRD Pilot (50 -165 psi, 340 - 1140 kPa) (155 psi Max 10", 1070 kPa Max DN250)

---

Check one  Standard - Copper Tubing and Brass Fittings  
 "ST" Option\* - Stainless Steel Tubing (included with SP option, only replaces Copper Tubing)  
 "SP" Option\* - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing)

---

Optional  "RV" Option - Pilot on Reverse Side

### UL & C-UL LISTED: (1-1/4" - 10", DN32 - DN250)

\*Adder to standard price applies

1747 Commerce Way  
Paso Robles, CA 93446  
Phone: 855-663-9876  
Fax: 805-237-7197

Customer Service Representatives available  
Monday through Friday 5:30 a.m. to 5:00 p.m., PST  
Fax completed forms to 805-237-7197, attention: Sales  
Call 855-663-9876, wilkinscs@zurn.com  
or visit us online at www.zurn.com

